





**HALL TWINSITE PIN OUTPUT DIAGRAM**


Best accuracy will be obtained using the calibration data in the table below:

Graduation	Nominal Reference Volts
E-Stop	0.291*
E	0.490
10	0.642
20	1.155
30	1.528
40	1.976
50	2.497
60	3.023
70	3.499
80	3.892

**REMOTE READY HALL EFFECT MODULE PIN  
OUTPUT DIAGRAM**


Best accuracy will be obtained using the calibration data in the table below:

Graduation	Nominal Reference Volts
E-Stop	0.318*
10	0.590
20	1.087
30	1.475
40	1.965
50	2.505
60	3.072
70	3.556
80	4.004

**Notes for TwinSite & Module :**

- **The Device is intended for supply voltage of 5 VDC, 4.5 to 5.5 VDC. With decrease in accuracy of only 1 to 2%, the supply voltage range can be extended to 3.5 to 6.0 VDC. The typical current draw is 4.5mA.**
- **The output is ratiometric, percent of supply voltage, 1:1 Ratio**
- **Settling time is 1.5 Microseconds and does not include any circuitry outside TwinSite or Module.**
- **Due to temperature compensation for magnet, voltage output will drift up to 40mV if power is applied for more than a few seconds .**
- **While maximum rated load is one mA, for best accuracy, the actual load should be 100 uA or less.**
- **Like many amplifiers, the output amplifier of the sender will become unstable when driving capacitive loads. These senders are usually stable with a maximum input resistance of 150 Ohms and with maximum load capacitance, including cable and load not over 0.3uF at room temperature. Careful design is required to minimize these factors. If they can not be eliminated , testing must be done to insure that the system operates correctly under all conditions.**
- **For Twinsite control drawing, see WD-566**
- **For wire attachment see DS-1014 and apply label 0115-01092 when installing wire.**
- **For Module control drawing see WD-570**
- **For wire attachment see DS-1349 & DS-1387 and apply label 0115-01096 when installing wire.**
- **For ratios other than 1:1 see DS-1368 thru DS-1371.**
- **For vertical tanks see DS-1396.**

**Note:**

Materials and specifications are subject to change without notice.  
Pressure ratings subject to change due to temperature and other environmental considerations.

\* To assure that indicator registers empty, set empty indication to at least 0.5 volts.